

**WE CLAIM AS OUR INVENTION:**

of:

1. A method for preparing an anatomical implant, comprising the steps  
intra-operatively generating a three-dimensional dataset of body tissue of a  
subject exhibiting a fault to be corrected by an implant from a series  
of two dimensional projections of the body tissue obtained from  
respectively different projection directions with a movable C-arm x-ray  
apparatus, but moving an x-ray source and a radiation receiver on a  
C-arm around said subject; and  
intra-operatively preparing said implant adapted for introduction into said  
subject from said three-dimensional dataset.
2. A method as claimed in claim 1 comprising acquiring a three-  
dimensional dataset which represents a bone structure of said subject.
3. A method as claimed in claim 1 comprising intra-operatively preparing  
said implant with an automated device which is supplied with said three-dimensional  
dataset.
4. An apparatus for preparing an anatomical implant comprising:  
a C-arm x-ray apparatus having a C-arm with an x-ray source and a radiation  
receiver mounted thereon, said C-arm x-ray apparatus intra-  
operatively generating a three-dimensional dataset of body tissue of  
a subject exhibiting a fault, to be corrected with an implant, by

pubA2

obtaining a series of two-dimensional projections of the body tissue from respectively different projection directions by moving said C-arm, with said x-ray source and said radiation detector thereon, around the body tissue; and

an implant-producing device which intra-operatively produces said implant from said three-dimensional dataset.

5. An apparatus as claimed in claim 4 wherein said dataset represents a bone structure, and wherein said implant is adapted to replace said bone structure.

6. An apparatus as claimed in claim 4 wherein said implant-preparing device is an automated device which is supplied with said three-dimensional dataset and automatically prepares said implant therefrom.